

YELLOW GAS LINE PTFE TAPE ▼

YELLOW GAS LINE PTFE TAPE is a high density PTFE Tape specifically used on natural gas, propane and butane lines .

PHYSICAL PROPERTIES:

Thickness:	0.1mm/0.004"
Width:	12mm(1/2") 19mm(3/4") 25mm(1")
Density:	0.80g/cm ³ to 1.80g/cm ³
Composition:	Min. 99% virgin PTFE, Max. 1% pigment
Temp. Range:	-450F(268C) to +500F (260C)
Pressure Rating:	up to 10,000PSI
Tensile Strength:	15N/mm ²
Elongation:	Min 50%
Storage:	Unlimited shelf life (less than 70F recommended)
Flammability:	Non-flammable



PINK PLUMBER LINE THREAD SEAL TAPE ▼

Pink Plumber Line Thread Seal Tape is a full density thread seal tape for used with piping in air, water, sewage, hydraulic lines and sprinkler systems.

PHYSICAL PROPERTIES:

Thickness:	0.1mm/0.004"
Width:	12mm(1/2") 19mm(3/4") 25mm(1")
Density:	1.20g/cm ³ to 1.50g/cm ³
Composition:	Min. 99% virgin PTFE, Max. 1% pigment
Temp. Range:	-450F(268C) to +500F (260C)
Pressure Rating:	up to 10,000PSI
Tensile Strength:	15N/mm ²
Elongation:	Min 50%
Storage:	Unlimited shelf life (less than 70F recommended)
Flammability:	Non-flammable



BLUE INDUSTRIAL THREAD SEAL TAPE ▼

Blue Industrial Thread Seal Tape is high quality and specially for industrial pipe .

PHYSICAL PROPERTIES:

Thickness:	0.1mm/0.004"
Width:	12mm(1/2") 19mm(3/4") 25mm(1")
Density:	0.8g/cm ³ to 1.20g/cm ³
Composition:	Min. 99% virgin PTFE, Max. 1% pigment
Temp. Range:	-450F(268C) to +500F (260C)
Pressure Rating:	up to 10,000PSI
Tensile Strength:	15N/mm ²
Elongation:	Min 50%
Storage:	Unlimited shelf life (less than 70F recommended)
Flammability:	Non-flammable



GREEN OXYGEN LINE PTFE TAPE ▼

Green Oxygen Thread Seal Tape is recommended for all oxygen lines.

PHYSICAL PROPERTIES:

Thickness:	0.1mm/0.004"
Width:	12mm(1/2") 19mm(3/4") 25mm(1")
Density:	1.20g/cm3 to 1.50g/cm3
Composition:	Min. 99% virgin PTFE, Max. 1% pigment
Temp.Range:	-450F(268C) to +500F (260C)
Pressure Rating:	up to 10,000PSI
Tensile Strength:	15N/mm2
Elongation:	Min 50%
Storage:	Unlimited shelf life (less than 70F recommended)
Flammability:	Non-flammable



GRAY STAINLESS STEEL ANTI-SEIZE PTFE TAPE ▼

Has nickel pigment colour added and recommended for all stainless steel pipe and fittings.

PHYSICAL PROPERTIES:

Thickness:	0.1mm/0.004"
Width:	12mm(1/2") 19mm(3/4") 25mm(1")
Density:	1.20g/cm3 to 1.80g/cm3
Composition:	Min. 99% virgin PTFE, Max. 1% pigment
Temp.Range:	-450F(268C) to +500F (260C)
Pressure Rating:	up to10,000PSI
Tensile Strength:	15N/mm2
Elongation:	Min 50%
Storage:	Unlimited shelf life (less than 70F recommended)
Flammability:	Non-flammable

